

DBMaker/DBMaster FAQ Document

Question:

How to use ESQL/C stored procedure in 4.3.3 bundle version? (DBMR 1912)

Answer:

Suppose the HOME directory is: **C:\dbmaker\43bundle**.

It will use some folders and files in 4.3.3 normal version, so user needs to copy them to related bundle folders.

By the following steps user can prepare environment for building ESQL/C stored procedure with 4.3.3 bundle.

Steps:

- (1) Register DBMaker bundle in regedit: register HOME and COMPILER for bundle.
- (2) Copy **dmppcc.exe** to bundle\bin (C:\dbmaker\43bundle\bin)
- (3) Copy **dmapi43.dll** to bundle\bin (C:\dbmaker\43bundle\bin)
- (4) copy bundle **dmconfig.ini** to bundle\bin (C:\dbmaker\43bundle\bin)
- (5) Copy the **templates** folder to bundle (C:\dbmaker\43bundle\templates)
- (6) Copy **include** folder from normal to bundle (C:\dbmaker\43bundle\include)
- (7) copy **lib** folder from normal to bundle (C:\dbmaker\43bundle\lib)
- (8) Modify **vc60.mak** in templates folder: modify path to used folder name; if other folders or files are used in **vc60.mak**, these folders/files also need to be copied to bundle folder.

For example:

C:\DBMaker\4.3\include => C:\dbmaker\43bundle\include

C:\DBMaker\4.3\lib => C:\dbmaker\43bundle\lib

Now, user can create and use ESQL/C stored procedure with 4.3.3 bundle.

Before that, please remove 4.3 normal versions to keep the environment clean.

Note: bundle **dmconfig.ini** and **dmapi43.dll** these two files exist in two folders, One is "C:\dbmaker\43bundle", another is "C:\dbmaker\43bundle\bin".

Email: <Support_RD@syscom.com.tw>